



NOTES:

1. MATERIALS AND FINISHES:
 BNC STR PLUG - BRASS, NICKEL PLATING
 SMA STR PLUG - BRASS, GOLD PLATING
 CABLE - RG 174
2. ELECTRICAL:
 A. IMPEDANCE: 50 OHM
3. PACKAGING:
 A. QUANTITY: SINGLE PACK
 B. MARKING: BAG TO BE MARKED
 "AMPHENOL RF, 95-850-249-XXX AND DATE CODE"

REVISIONS				
REV	DESCRIPTION	DATE	ECN	APPR
A	RELEASE TO MFG.	25-JUN-20	15249	KR



LENGTH TABLE		
PART NUMBER (IMPERIAL)	PART NUMBER (METRIC)	LENGTH 'L' IN INCHES [METERS]
95-850-249-003	-	3.00 [0.076]
95-850-249-006	-	6.00 [0.152]
95-850-249-012	-	12.00 [0.006]
95-850-249-018	-	18.00 [0.457]
95-850-249-024	-	24.00 [0.610]
95-850-249-036	-	36.00 [0.914]
-	95-850-249M100	39.37 [1.000]
95-850-249-072	-	72.00 [1.829]
-	95-850-249M200	78.74 [2.000]
-	95-850-249M300	118.11 [3.000]

TOLERANCE TABLE	
LENGTH IN INCHES/FT [METERS]	TOLERANCE
0" - 23.90" [0 - 0.607]	±0.25" [0.006]
24.00" - 59.00" [0.610 - 1.499]	±0.50" [0.013]
5.0' - 24.9' [1.524 - 7.617]	±2.5%
25.0' & UP [7.620 & UP]	±5.0%

DESIGN REQUIREMENTS:

- | | |
|---|--|
| <input checked="" type="checkbox"/> FREQUENCY: DC - 6 GHz | <input checked="" type="checkbox"/> CONTINUITY |
| <input type="checkbox"/> VSWR: _____ 1 MAX. | <input checked="" type="checkbox"/> HI-POT: 750 VRMS |
| <input type="checkbox"/> INS. LOSS: _____ dB MAX | <input type="checkbox"/> OTHER |

CUSTOMER OUTLINE DRAWING
 ALL OTHER SHEETS ARE FOR INTERNAL USE ONLY

NOTICE: These drawings, specifications, or other data (1) are, and remain the property of Amphenol corp. (2) must be returned upon request; and (3) are confidential and not to be disclosed to any person other than those to whom they are given by Amphenol Corp. The furnishing of these drawings, specifications, or other data by Amphenol Corp., or to any other person to anyone for any purpose is not to be regarded by implication or otherwise in any manner licensing, granting rights to permitting such holder or any other person to manufacture, use or sell any product, process or design, patented or otherwise, that may in any way be related to or disclosed by said drawings, specifications, or other data.

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE METRIC [INCHES] AND TOLERANCES ARE:
 <0.5mm = ±0.05mm [-0.020 = ±0.002]
 >0.5 - 6mm = ±0.1mm [0.020 - 0.236 = ±0.004]
 >6.00 - 30mm = ±0.2mm [0.236 - 1.181 = ±0.008]
 >30.00 - 120mm = ±0.3mm [1.181 - 4.725 = ±0.012]

MATERIAL
 SEE NOTES

TITLE
 BNC STR PLUG TO SMA STR PLUG USING RG 174 CABLE VARIOUS LENGTH

<p>Amphenol RF</p>		REV				
		<p>SIZE B</p>				
		<table border="0"> <tr> <td>DRAWING NO.</td> <td>95-850-249-XXX</td> </tr> <tr> <td>ITEM NO.</td> <td>95-850-249-XXX</td> </tr> <tr> <td>PART NO.</td> <td>95-850-249-XXX</td> </tr> </table>	DRAWING NO.	95-850-249-XXX	ITEM NO.	95-850-249-XXX
DRAWING NO.	95-850-249-XXX					
ITEM NO.	95-850-249-XXX					
PART NO.	95-850-249-XXX					

THIRD ANGLE PROJ. REFERENCE EAR# 9922

ENGINEER KARTHIK R DATE 03-JUN-20

SHEET NO. 2 OF 2 SCALE: 2.2:1.0

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Amphenol:

[095-850-249-003](#) [095-850-249-006](#) [095-850-249-012](#) [095-850-249M300](#) [095-850-249-018](#) [095-850-249-024](#) [095-850-249-036](#) [095-850-249-072](#) [095-850-249M100](#) [095-850-249M200](#)